

SINCE 1925

**KEYSTONE**

SAFETY ⇄ CLEANROOM PRODUCTS

# 1422A TYVEK® FILLING NEEDLE BAGS WITH DRAWSTRING CLOSURE



## TYPICAL APPLICATION & CHARACTERISTICS:

- Designed for steam sterilization
- Tyvek® on both sides for maximum breathability during sterilization
- Eliminates need to cut material and the use of autoclave tape
- Fast and consistent for equipment preparation area
- Creates secondary level of protection during aseptic presentation of equipment
- Sealed seams eliminate sewing threads and greatly reduce particulates
- Resists tearing and punctures
- Superior microbial barrier
- Lint-free
- Manufactured and packaged in ISO certified cleanrooms
- Certificates of Conformance sent with all shipments
- Made in USA

## MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Seal Strength	N/mm	F-88	>.88
Basis Weight	g/m2	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700
Hydrostatic Head	cm h2o	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm2)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	c°		135

SINCE 1925

**KEYSTONE**

SAFETY ⇄ CLEANROOM PRODUCTS

# 1422A TYVEK® FILLING NEEDLE BAGS WITH DRAWSTRING CLOSURE



KEYSTONE PART NUMBER	DIMENSIONS
BGT2A0105D	1" X 5"
BGT2A0109D	1" X 9"
BGT2A0206D	2" X 6"
BGT2A02503D	2.5" X 3"
BGT2A0308D	3" X 8"
BGT2A0314D	3" X 14"