



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Characteristics



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Static free and ESD safe
- EMI/RFI Shielded
- TELECOM package available
- 4-stage filtration system includes an ULPA Filter (U15), double cloth filter, and disposable filter bags. An internal OSHA compliant HEPA filter (H14) is available as a 5th stage of filtration
- Designed for use in contamination controlled environments
- Powerful dual speed Thru-Flow motor
- For dry recovery only
- Made entirely of chrome-polished steel
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

Specifications

| EMI-CWR | 110110A |
|--------------------------------------|-----------------------|
| Model Name | EMI-CWR |
| Type | Electric |
| Tension | 120 V |
| Frequency | 60 Hz |
| Phase | Single |
| Wattage | 1000 W |
| Power | 1.3 HP |
| Amperage | 8.5 A |
| Air Flow | 120 CFM |
| Vacuum Pressure | 95 " H ₂ O |
| Sound Level | 70 dB(A) |
| Type of Power Outlet | 120V |
| Suction Inlet Port | 1.5 " |
| Cart Type | 4 Wheel Dolly (4W) |
| Filter Cleaning | None |
| Dust Recovery Tank | 4 Gal |
| Dry Recovery - Disposable Filter Bag | 2.5 gal. |
| Length | 15 " |
| Width | 17 " |
| Height | 28 " |
| Weight (Vacuum Only) | 35 lb. |
| Cord Length | 35 ft. |

Please note that specifications are subject to change without notice


Use only recommended tools & accessories



Tools and Accessories for EMI-CWR - Included



#211028 Paper Filter Recovery Bags for model EMI-CWR
(Package of 5) - Included



EMI SUPPRESSION / RFI SHIELDING



ULPA Filter - Included



Stainless steel holding bracket - Optional